



## Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System  
Date of Revision: 05/17/2001 Revision: 03

### Section 1 - Chemical Product and Company Identification

1.1 Product Name: **Late Model +**

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmhurst, TX 78112, 210.635.7744

1.4 Recommended Use: Racing Fuel

1.5 **RESTRICTIONS on USE** **THIS FUEL IS FOR RACING VEHICLE USE ONLY!**

**NOT LEGAL FOR STREET DRIVEN MOTOR VEHICLE**

1.6 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

1.7 See Section 16.3 for CHEMTREC in Country Emergency Numbers.

### Section 2 - Hazards Identification

#### 2.1 GHS HAZARD

##### Hazard Classes

**Highly Flammable liquid/vapor**

**Specific Target Organs toxicity single exposure**

**Specific Target Organs repeated exposure**

**Eye Irritation**

**Skin Irritation**

**Acute Toxicity (Oral)**

**Mutagenicity**

**Carcinogen**

**Reproductive Toxicity**

**Aspiration Hazard**

**Toxic to Aquatic Life Long Lasting Effects**

##### Hazard Categories

**Category 2**

**Category 3**

**Category 2**

**Category 2A**

**Category 2**

**Category 3**

**Category 1B**

**Category 1B**

**Category 2**

**Category 1**

**Category 2**

2.2 Signal Word: **Danger**

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System



Flame

Health

Irritant

Aquatic

### 2.3 Pictograms:

### 2.4 Hazard Statements

#### PHYSICAL HAZARDS:

H225: Highly flammable liquid and vapor.

#### HEALTH HAZARDS:

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

#### ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long-lasting effects.

#### PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use.  
**READ SDS BEFORE USE.**

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks and open flames-  
No smoking.

P233: Keep the container tightly closed.

P240: Ground or bond container and receiving equipment.

P241: Use explosion-proof equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe vapors.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, clothing, and eye protection.

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

### RESPONSE STATEMENTS:

**P301 +P310+ P331: IF SWALLOWED:**  
Immediately call a poison center or doctor. DO NOT induce vomiting.  
**P303+P361+P353: IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water.  
**P308+P313:** If exposed or concerned, get medical attention.  
**H314:** Get medical attention if you feel unwell.  
**P362+P363+P364: IF ON CLOTHING,** take off contaminated clothing and wash it before reuse.  
**P370+P378:** In case of fire, use foam, carbon dioxide, dry chemical to extinguish a fire  
**P391** Collect spillage.

### STORAGE STATEMENTS:

**P403+P235:** Store in a well-ventilated place. Keep cool.  
**P405:** Store locked up.

### DISPOSAL STATEMENTS:

**P501:** Dispose of content and container following local, regional, national or international regulations.

**2.5 Hazards not otherwise classified (HNOC) or not covered by GHS:** Repeated exposure may cause skin dryness or cracking

## Section 3 - Composition / Information on Ingredients

### 3.1

CAS#	EC#	Chemical Names	Percent	Other Identifiers
N/A	N/A	Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	99.7%	Not Classified
78-00-2	201-075-4	Tetraethyl plumb	≤ 0.3%	Acute Tox. 2 H300, Acute Tox. 1 H310, Acute Tox. 2 H330, Repr. 1A H360, STOT RE 2 H373, Aquatic Chronic 1 H410, Aquatic Acute 1 H400

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

### 3.2 Blend

Chemical Names	CAS#	EC#	GHS Harmonized Classification
1,1,2-Trimethylethane	78-78-4	201-142-8	Flam. Liq. 1 H224, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Repr. 2 H361, STOT RE 2 H373
2, 2, 4-Trimethylpentane	540-84-1	208-759-1	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 1 H410, Aquatic Acute 1 H400
Alkylate Full Range	64741-64-6	265-066-7	Asp. Tox. 1 H304, Muta. 1B H340, Carc. 1B H350, Aquatic

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** Per OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and applicable to the hazards identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

**4.1 Eye:** Contact with the eyes can irritate. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

**4.2 Skin:** Prolonged and repeated liquid contact can cause defatting and drying of the skin and lead to irritation and dermatitis.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

**Ingestion:** Do NOT induce vomiting. Get medical aid immediately.

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

**4.4 Inhalation:** Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

**4.5 After first aid, get appropriate paramedic or community medical support.** The severity of outcome following exposure may be related to the time between the exposure and treatment rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

**4.6 Note to Physicians:** If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, per OSHA's Trade Secret Regulations, as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

### Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire.

**5.2 Hazardous Combustion Products:** Avoid fumes of burning products.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**5.4 Fire Fighting Equipment/Instructions:** Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

### Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Ventilate area highly flammable. Spillages of the liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

**6.2 Spills:** Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

### Section 7 - Handling and Storage

**7.1 Handling Precautions:** Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin, or clothing. Keep container tightly closed. Avoid inhalation.

**7.2 Storage Requirements:** Store in a tightly closed container in a cool, dry, and well-ventilated area.

# Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## Section 8 - Exposure Controls / Personal Protection

### 8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	20 - 300 ppm TWA	20- 300 ppm TWA
Tetraethyl plumb	0.1mg/m3	0.75mg/m3

### 8.2.

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

**8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder them before reuse.  
Remove this material from your shoes and clean personal protective equipment.

### 8.5 Personal protective equipment

#### 8.5.1 Respiratory protection

Where risk assessment shows, air-purifying respirators are appropriate, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### 8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

#### 8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### 8.5.4 Skin and body protection

Impervious clothing, Flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### 8.6 Protective Clothing Pictograms



## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

### Section 9 - Physical and Chemical Properties

#### 9.1

**Physical State:** Liquid

**Appearance:** Aqua

**Odor:** Aromatic Hydrocarbon Odor

**Vapor Pressure:** Not Available

**Vapor Density (Air=1):** >1

**Specific Gravity (H<sub>2</sub>O=1,):** 0.71

**Relative Density:** Not Available

**Odor Threshold:** Not Available

**Flammability (solid, gas):** Not applicable.

**Evaporation rate:** Not Available

**Partition coefficient octanol/water:** Not Available

**Water Solubility:** Insoluble

**Melting point/freezing point:** Not Available

**Flash Point:** -40°F (-40°C) close cup

**Boiling Point / Range:** 97.7 – 402.1°F  
(36.5 – 205.6°C)

**Lower Explosive Limits (vol % in air):** 1%

**Upper Explosive Limits (vol % in air):** 8%

**Viscosity:** <20.5mm<sup>2</sup>/s 104°F,40°C

**Auto ignition Temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** None

### Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents.

**10.4 Hazardous Decomposition Products:** Combustion produces carbon monoxide and carbon dioxide.

**10.5 Conditions to Avoid:** Avoid heat, sparks, open flames, and other ignition sources.

### Section 11- Toxicological Information

#### 11.1

Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 2173 mg/kg

ATE (Dermal): 2380 mg/kg

ATE (Inhalation vapor/mist): 7.27 mg/l vapor

**11.1.1** OECD Guideline Test results found in the European Chemical Agency Database show that no components of this product cause Toxic Oral Toxicity.

**11.1.2** OECD Guideline Test results found in the European Chemical Agency Database show that no product components cause Harmful Dermal Toxicity.

**11.1.3** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause Toxic Inhalation Toxicity.

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

**11.3 Aspiration Hazard:** European Chemical Agency Database shows that components of this product may be fatal if swallowed and enters the airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause genetic defects.

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause skin irritation. Repeated exposure may cause skin dryness or cracking.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that no product components cause serious eye irritation. However, it still may irritate your eyes.

**11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause damage to fertility or the unborn child.

**11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency Database show no product components to cause skin sensitivity.

**11.9 Respiratory Sensitization** OECD Guideline Test results found in the European Chemical Agency Database show no product components to cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** European Chemical Agency Database shows that components of this product may cause damage to the central nervous system (CNS).

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains chemicals that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

**11.12 Signs and Symptoms:** Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components can cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Not classifiable as a human carcinogen	Not classifiable as a human carcinogen	Not listed	Not listed
Tetraethyl plumb	Not classifiable as a human carcinogen	Not classifiable as a human carcinogen	Reasonably anticipated to be a human carcinogen	No component of this product present at levels greater than or equal to 0.1%

## Section 12 - Ecological Information

### 12.1

Product Name	Results	Species	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		
Tetraethyl plumb	LC50 0.23 mg/l	Fish	96 hours

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show components of this product to cause long-term toxicity to aquatic life.

**12.2 Mobility:** Floats on water.

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.


**12.5 Other adverse effects:** Inconclusive technical data.

### Section 13 - Disposal Considerations

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be completely emptied before discard. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

### Section 14 - Transport Information

#### 14.1 DOT Transport Information



**ID No.:** UN 1203

**Shipping Name:** Gasoline

**Hazard Class:** 3

**Packing Group:** II

**Label:** Flammable

**Placard:** Flammable

**Marking:** MARINE POLLUTANT Alkylate Full Range when shipping ground greater than 119 gallons single container or any quantity by water

#### 14.2 IMDG Transport Information



**ID No.:** UN 1203

**Shipping Name:** GASOLINE

**Hazard Class:** 3

**Packing Group:** II

**Flash Point:** (-40°C c.c.)

**EmS Number:** F-E, S-E

**Label:** Flammable


**Placard:** Flammable

**Marking:** Marine Pollutant Alkylate Full Range

# Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

## 14.3 UN Dangerous Goods Transport Information



**ID No.:** ID No.: UN1203  
**Shipping Name:** Gasoline  
**Hazard Class:** 3  
**Packing Group:** II  
**Label:** Flammable  
**Placard:** Flammable  
**Marking:** Marine Pollutant Alkylate Full Range

## Section 15 - Regulatory Information

### 15.1 US Regulations

**US. Toxic Substances Control Act:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
108-88-3	Phenylmethane	18%
78-00-2	Tetraethyl plumb	0.3%
110-54-3	n-Hexane	At demines% limits
100-41-4	Ethylbenzene	At demines% limits

This information must be included in all SDSs that are copied and distributed for this material.

**CERCLA Hazardous Substances and corresponding RQs:** Phenylmethane 1000lbs, Tetraethyl plumb 10lbs., 2, 2, 4-Trimethylpentane 1000lbs., N-Hexane 5000 lbs, Ethylbenzene 1000 lbs.

**SARA Community Right-to-Know Program:** All components of this blend.

**Clean Water Act:** None

**Clean Air Act:** 1,1,2-Trimethylethane

**OSHA:** All ingredients are regulated by 29 CFR 1910.1200.

### State Regulations

**California prop. 65:**



This product can expose you to chemicals Ethylbenzene CAS # 100-41-4, Phenylmethane CAS # 188-88-3, and n-Hexane CAS # 110-54-3, which are known to the State of California to cause cancer and birth defects, or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

### 15.2 International Regulations:

**Australian Inventory of Chemical Substances:** All components of this product are on the Inventory or are exempt from Inventory requirements

**National Existing Chemical Inventory in Taiwan:** All components of this product are on Inventory or are exempt from Inventory requirements

**Philippine Inventory of Chemicals and Chemical Substances** All components of this product are on the Inventory or are exempt from Inventory requirements

**China Existing Chemical Inventory:** All components of this product are on the Inventory or are exempt from Inventory requirements

## Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and on the condition that they assume the risk of their use.

**16.2 References:** CHEMpendium database of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller online, European Chemical Agency Database and MSDS and SDS of chemicals in this mixture.

### 16.3 CHEMTREC in-country emergency dial numbers:

County	Greeting Language	City	Local number	Toll-Free number
Argentina	Latin American Spanish	Buenos Aires	54-1159839431	
Brazil	Portuguese	Rio De Janeiro	55-2139581449	
Brazil	Portuguese	Sao Paulo	55-1143491359	
Brazil - Toll-Free	Portuguese		0800 892 0479	0800 892 0479
Cayman Islands	English	Local (National)	345-749-8392	
Chile	Latin American Spanish	Santiago	56 2 2581 4934	
Colombia	Latin American Spanish		01800-710-2151	01800-710-2151
Costa Rica	Latin American Spanish		506-40003869	

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

Dominican Republic	Latin American Spanish	Santo Domingo	1 (829) 956-7588	
El Salvador	Latin American Spanish	San Salvador	503 2136 7633	
Grenada	English	St George	1 (473) 230-0165	
Guinea	French		224 660 71 03 00	
Mexico	Latin American Spanish		01-800-681-9531	01-800-681-9531
Panama	Latin American Spanish		507-8322475	
Peru	Latin American Spanish	Lima	51-17071295	
Trinidad and Tobago	English	National Number	1-868-224-5716	

County	Greeting Language	City	Local number	Toll-Free number
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141
Indonesia	Indonesian		001-803-017-9114	001-803-017-9114
Israel	Hebrew	Tel Aviv	972-37630639	
Japan	Japanese	Tokyo	81-345209637	
Malaysia	Malay	Kuala Lumpur	60-392125794	1-800-815-308
Philippines	Tagalog	Manila	+63 2 8395 3308 and 1-800-1-116-1020	1-800-1-116-1020
Russia	Russian		8-800-100-6346	8-800-100-6346
Saudi Arabia	Arabic and English		966-8111095861	
Singapore	English and Mandarin		65-31581349	800-101-2201
South Korea	Korean			003-0813-2549 and 080-822-1374
Taiwan	Mandarin	Taipei	886-2-7741-4207	00801-14-8954
Thailand	Thai		001-800-13-203-9987	001-800-13-203-9987
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141

County	Greeting Language	City	Local number	Toll-Free number
Australia	English	Sydney	61-290372994	
New Zealand	English	Auckland	64-98010034	

## Late Model +

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System

County	Greeting Language	City	Local number	Toll-Free number
South Africa	English	None	0-800—983-611	0-800—983-611

**16.4 SDS Preparation Date** 12/09/2015

**SDS Previous Issue Date:** None

**SDS Revision Date:** 02/20/2019 Revised Sections: 3,8,11,14,15,16

**SDS Revision Date:** 09/14/2020 Revised Sections: 2,3,8,11,13,15,16

**SDS Revision Date:** 05/17/2021 Revised Sections: 2,3,4,8,9,11, 15,16

Prepared by SJC Compliance Education, Inc

1319 Varese Dr.

Pearland, TX.

[steve@sjcedu.org](mailto:steve@sjcedu.org)