



XR Series 8 Hole Channel Hitch Mount Drop & Rise + Rating Guide: (Add 2" if using 10-Hole Frame)

- **Combo Ball:** 4" Rise to 4" Drop | 2-5/16" ball rated at 20,000 lbs & 2" ball rated at 10,000 lbs.
- **Drop Ball:** 0" Rise to 7-1/2" Drop | 2-5/16" ball rated at 20,000 lbs & 2" ball rated at 10,000 lbs.
- **Raised Ball:** 5" Rise to 3" Drop | 2-5/16" ball rated at 20,000 lbs & 2" ball rated at 10,000 lbs.
- **Bolt on Pintle Hook:** 3.5" Rise to 8.5" Drop | 10-Ton 20,000 lbs.
- **Channel Style Pintle Hook:** 1" Rise to 7" Drop | 10-Ton 20,000 lbs.
- **Bolt on Pintle & Ball:** 3.5" Rise to 8.5" Drop | 8-Ton 16,000 lbs. (2" Ball is 10,000 lbs).
- **Channel Style Pintle & Ball:** 1" Rise to 7" Drop | 8-Ton 16,000 lbs. (2" Ball is 10,000 lbs).
- **Drawbar:** 4" Rise to 4" Drop | 20,000 lbs.
- **Clevis Mount:** 1-1/2" Rise to 6-1/2" Drop | 20,000 lbs.
- **Sway Bar Mounts:** Same Rating as Like Type Mount Listing Above

Safety Notice: Towing capacity is limited by lowest rated component. Never exceed max for any of the components you are using. If the coupler rating is 8,000 lbs and the hitch is 12,000 lbs, then don't tow over 8,000 lbs.